



(4) 3200 1B-RATED DS-4UA444 LIFTING EMBEDS

(4) 1 5/8" X 3/4" X 40" UNISTRUT (TYP 4)
 (2) Ø1 1/2" LIFTING HOLES
 (8) Ø5" KNOCKOUTS (FRONT & BACK)

(4) PULLING IRONS

(4) Ø4" KNOCKOUTS (EACH SIDE)
 (7) Ø5" KNOCKOUTS (EACH SIDE)

Ø8" SUMP

TOP SLAB (WPE11T)
 *Ø24" HOLE
 *Ø30" HOLE
 *Ø36" HOLE
 *SOLID LID
 *36" X 36" H20 HATCH (LIGHT TRAFFIC ONLY)
 *TRANSFORMER PAD MOUNT

NOTES:
 REINFORCEMENT:
 -#4 BAR @ 6" O.C.E.W. IN LID
 -#4 BAR @ 12" O.C.E.W. IN BASE



**2215 E. BROOKLYN AVE
 SPOKANE, WA 99217
 TOLL FREE 1-800-888-4573
 (509) 325-4573 FAX (509) 325-5098
 SPOKANE - LEWISTON - YAKIMA
 www.wilbertprecast.com**

TITLE: WPE11B UTILITY VAULT W/36" X 36" HATCH			
SIZE B	DWG. NO. WPE11B TH	SCALE: NTS	DATE: 3/20/2019

DRAWN BY:
CEB